

# Leica RTC360 3D Reality Capture Solution

Fast. Agile. Precise.



## Fast

The Leica RTC360 laser scanner makes 3D reality capture faster than ever before. With a measuring rate of up to 2 million points per second and advanced HDR imaging system, the creation of colored 3D point clouds can be completed in under 2 minutes. Plus, automated targetless field registration (based on VIS technology) and the seamless, automated transfer of data from site to office reduce time spent in the field and



## Agile

Small and lightweight, the Leica RTC360 scanner's portable design and collapsible tripod mean it's compact enough to fit into most backpacks, ready to be taken anywhere. Once on-site, easy-to-use one-button operation makes for fast, hassle-free scanning.



## Precise

Low noise data allows for better images, resulting in crisp, high-quality scans that are rich in detail and ready for use in a range of applications. Combined with Cyclone FIELD 360 software for automated registration in the field, the Leica RTC360 scanner offers outstanding precision that can be checked on-site.



leica-geosystems.com



- when it has to be **right**

**Leica**  
Geosystems

# Leica RTC360 Product Specifications

<b>GENERAL</b>	
3D laser scanner	High-speed 3D laser scanner with integrated HDR spherical imaging system and Visual Inertial System (VIS) for real time registration
<b>PERFORMANCE</b>	
Data acquisition	< 2 min for complete full dome scan and spherical HDR image at 6 mm @ 10 m resolution
Real time registration	Automatic point cloud alignment based on real time tracking of scanner movement between setups based on Visual Inertial System (VIS) by video-enhanced inertial measurement unit
Double scan	Automatic removal of moving objects
Check & Adjust	Field procedure for targetless checking of angular parameters
<b>SCANNING</b>	
Distance measurement	High-speed, high dynamic time of flight enhanced by Waveform Digitizing (WFD) technology
Laser class	1 (in accordance with IEC 60825-1:2014), 1550nm (invisible)
Field of view	360° (horizontal) / 300° (vertical)
Range	Min. 0.5 - up to 130 m
Speed	Up to 2,000,000 pts / sec
Resolution	3 user selectable settings (3 / 6 / 12 mm @ 10 m)
Accuracy*	Angular accuracy 18" Range accuracy 1.0 mm + 10 ppm 3D point accuracy 1.9 mm @ 10 m 2.9 mm @ 20 m 5.3 mm @ 40 m
Range noise**	0.4 mm @ 10 m, 0.5 mm @ 20 m
<b>IMAGING</b>	
Camera	36 MP 3-camera system captures 432 MPx raw data for calibrated 360° x 300° spherical image
Speed	1 minute for full spherical HDR image at any light condition
HDR	Automatic, 5 brackets
<b>NAVIGATION SENSORS</b>	
Visual Inertial System	Video enhanced inertial measuring system to track movement of the scanner position relative to the previous setup in real time
Tilt	IMU based, Accuracy: 18" (for upright and upside down setups with +/- 10° inclination)

Additional sensors	Altimeter, Compass, GNSS
<b>OPERATION</b>	
On scanner	Touch-screen control with finger touch, full color WVGA graphic display 480 x 800 pixels
Mobile devices	Leica Cyclone FIELD 360 app for iOS and Android tablet computers and smartphones including: - Remote control of scan functions - 2D & 3D data viewing - Tagging - Automatic alignment of scans
Wireless	Integrated wireless LAN (802.11 b/g/n)
Data storage	Leica MS256, 256GB exchangeable USB 3.0 flash drive
<b>DESIGN &amp; PHYSICAL</b>	
Housing	Aluminium frame and sidecovers
Dimensions	120 mm x 240 mm x 230 mm / 4.7" x 9.4" x 9.1"
Weight	5.35 kg / 11.7 lbs, nominal (without batteries)
Mounting mechanism	Quick mounting on 5/8" stub on lightweight tripod / optional tribrach adapter / survey tribrach adapter available
<b>POWER</b>	
Internal battery	2 x Leica GEB364 internal, rechargeable Li-Ion batteries. Duration: Typically up to 4 hours Weight: 340 g per battery
External	Leica GEV282 AC adapter
<b>ENVIRONMENTAL</b>	
Operating temperature	-5° to +40°C
Storage temperature	-40° to +70°C
Operating low temperatures****	-10° to +40°C
Dust/Humidity***	Solid particle / liquid ingress protection IP54 (IEC 60529)



Leica Cyclone FIELD 360



Leica Cyclone REGISTER 360



Leica ScanStation P50

All specifications are subject to change without notice.

All accuracy specifications are on a level of confidence of 68% according to the Guide of the Expression of Uncertainty in Measurement (JCGM100:2008) unless otherwise noted.

\* At 89% albedo.

\*\* For single shot measurements

\*\*\* For upright and upside down setups with a +/- 15° inclination

\*\*\*\* Extended low temperature operation is possible to -10°C if internal temperature is at or above -5°C when powered on. For extended low temperature measurement, it is recommended that QA procedures are followed.

Scanner: Laser class 1 in accordance with IEC60825:2014

iPhone and iPad are trademarks of Apple Inc.

Android is a trademark of Google.



## Your Trusted Active Customer Care

Active Customer care is a true partnership between Leica Geosystems and its customers. Customer Care Packages (CCPs) ensure optimally maintained equipment and the most up-to-date software to deliver the best results for your business. The myWorld @ Leica Geosystems customer portal provides a wealth of information 24/7.

Illustrations, descriptions and technical specifications are not binding and may change. All rights reserved. Printed in Switzerland - Copyright Leica Geosystems AG, Heerbrugg, Switzerland 2018. 872751enus - 04.22

**Leica Geosystems AG**  
Heinrich-Wild-Strasse  
9435 Heerbrugg, Switzerland  
+41 71 727 31 31

- when it has to be **right**